



1280 N Red Gum Street Anaheim, CA 92806 • 714-632-1400

250 CFM Makotherm (MV) Thermal-Catalytic Oxidizer / Medium Vacuum System

Standard Features:

- Small Footprint Skid Mounting
- Entrained Liquid Separator
- Dilution / Process Valves
- Stainless Steel Transfer Pump
- Positive Displacement Blower
- Blower Re-circulation Valve
- 10 Horsepower TEFC Motor
- Sound Enclosure
- Oxidizer Chamber
- Excess Air Packaged Burner
- Supplemental Fuel Train
- Flame Arrestor
- Digital Temperature Controller
- Digital Dilution Controller
- Pitot Tube / Pressure Transmitter
- Digital Chart Recorder



Standard Options:

Trailer Mounted System • Stainless Steel Heat Exchanger
Platinum Coated Catalyst Cell • Remote Telemetry
Totally Enclosed System • Single Phase System
UL Listed Electrical Enclosure E306379

Standard Performance Specifications:

Skid Dimensions = 5' Width x 5' Length x 13' Height

3/16" Heavy Duty Steel Construction Throughout

Electrical Requirement = 208/240 Volt/3 Phase/60 Amp

Electrical Requirement = 208/240 Volt/1 Phase/100 Amp

Fuel Requirement = LPG or Natural Gas / 5 PSI / 400SCFH

